



2632EX EXPLOSION PROOF SCISSOR LIFT

| SPECIFICATIONS | | |
|----------------------------------|----------------------|-------------|
| Working Height | 32 ft | 9.8 m |
| Raised Platform Height | 26 ft | 7.9 m |
| Lowered Platform Height | 45 in | 1.1 m |
| Platform Size (inside) | 28 x 84 in | 0.7 x 2.1 m |
| Platform Capacity | 500 lbs | 227 kg |
| Overall Width | 32 in | 0.8 m |
| Overall Length | 108 in | 2.75 m |
| Stowed Height | 84.7 in | 2.2 m |
| Deck Extension | 3 ft | 0.92 m |
| Ground Clearance (Stowed) | 3.5 in | 8.9 cm |
| Ground Clearance (Raised) | 0.75 in | 1.9 cm |
| Wheelbase | 69 in | 1.8 m |
| Inside Turning Radius | 50 in | 1.3 m |
| Outside Turning Radius | 108 in | 2.7 m |
| Drive Speed (Stowed) | 1 mph | 1.6 km/h |
| Drive Speed (Raised) | 0.5 mph | 0.8 km/h |
| Batteries | 4 x 6V 250 Amp-hr | |
| Charger | 20 Amp Automatic SCR | |
| Specifications Subject to Change | | |



SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 26 ft Platform Height
- 32 ft Working Height
- 28 x 84 in Platform Size
- 3.5 in Ground Clearance
- 500 lb Platform Capacity
- 3 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

OPTIONS*

- Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform

*May Change Capacity

