



# 3247EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS		
Working Height	38 ft	11.6 m
Raised Platform Height	32 ft	9.8 m
Lowered Platform Height	48.5 in	1.2 m
Platform Size (inside)	42 x 84 in	1.1 x 2.1 m
Platform Capacity	700 lbs	318 kg
Overall Width	47 in	1.2 m
Overall Length	108 in	2.75 m
Stowed Height	88 in	2.2 m
Deck Extension	4 ft	1.2 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	0.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	47.5 in	1.2 m
Outside Turning Radius	93.5 in	2.4 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Batteries	4 x 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	
Specifications Subject to Change		



## SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

## STANDARD EQUIPMENT

- 32 ft Platform Height
- 38 ft Working Height
- 42 x 84 in Platform Size
- 3.5 in Ground Clearance
- 700 lb Platform Capacity
- 4 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

## OPTIONS\*

- Padded Aircraft Rails
- Vertical Access Aid
- Explosion Proof Work Lights
- 1/2" Airline to Platform

\*May Change Capacity

