



4392EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS		
Working Height	49 ft	14.94 m
Raised Platform Height	43 ft	13.11 m
Lowered Platform Height	75.5 in	1.92 m
Platform Size (inside)	71.7 x 171.7 in	1.82 x 4.4 m
Platform Capacity	2,000 lbs	907 kg
Overall Width	90.6 in	2.3 m
Overall Length	177 in	4.5 m
Stowed Height (Rails Up)	119 in	3.02 m
Stowed Height (Rails Down)	84 in	2.13 m
Deck Extension	5 ft	1.5 m
Ground Clearance	10 in	26 cm
Wheelbase	119 in	3.0 m
Inside Turning Radius	131 in	3.33 m
Drive Speed (Stowed)	3.5 mph	5.6 km/h
Drive Speed (Raised)	0.6 mph	1 km/h
Batteries	8 x 6V 420 Amp-hr	
Charger	Automatic SCR	
Specifications Subject to Change		



SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 43 ft Platform Height
- 49 ft Working Height
- 72 x 172 in Platform Size
- 10 in Ground Clearance
- 2,000 lb Platform Capacity
- 5 ft Extendable Deck
- 500 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

OPTIONS*

- Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform
- 5 ft Powered Extendable Deck
- Dual 5 ft Roll-out or Powered Extendable Decks
- Remote Mount 600 Amp Charger & Battery
- Lithium Ion Battery
- FMR System Fault Monitoring and Recording

*May Change Capacity

