



T40EX EXPLOSION PROOF TELESCOPIC BOOM LIFT

SPECIFICATIONS		
Working Height	45 ft	13.72 m
Platform Height	40 ft	12.19 m
Platform Size	36 x 96 in	.91 x 2.44 m
Platform Capacity	1,000 lbs	453.59 kg
Overall Width	7 ft 7 in	2.31 m
Stowed Height	8 ft 1 in	2.47 m
Stowed Length	29 ft 3in	8.91 m
Ground Clearance	1 ft	0.31 m
Tailswing	2 ft 10 in	86 m
Inside Turning Radius	6 ft 5 in	1.96 m
Outside Turning Radius	15 ft 8 in	4.78 m
Jib Range of Articulation	6 ft, 130°	
Gross Weight (Est)	14,520 lbs	6,586 kg
Platform Rotation	180° Hydraulic	
Batteries	48v DC 650 Amp-Hr Battery	
Specifications Subject to Change		



**Image shown with the Soft Touch System option.*

SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 40 ft Platform Height
- 45 ft Working Height
- 36 x 96 in Platform Size
- 1 ft Ground Clearance
- 1,000 lb Platform Capacity
- Proportional Hydraulic Controls
- Platform Battery Condition Indicator
- 650 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm
- 1/2" Airline to Platform

OPTIONS

- Soft Touch System
- Fall Arrest System
- FMR System Fault Monitoring and Recording

